

### Router Modes

**Router>**: User mode = Limited to basic monitoring commands

**Router#**: Privileged mode (exec-level mode) = Provides access to all other router commands

**Router(config)#**: global configuration mode = Commands that affect the entire system

**Router(config-subif)#**: subinterface mode = Commands that affect subinterfaces

**Router(config-line)#**: line mode = Commands that affect in lines modes (console, vty, aux...)

**Router(config-router)#**: router configuration mode

### Changing switch hostname

```
Switch(config)# hostname SW1
```

### Configuring passwords

```
SW1(config)# enable secret nutty !MD5 hash  
SW1(config)# enable password 1234
```

### Encrypting passwords

```
SW1(config)# service password-encryption
```

### Working environment

```
SW1(config)# no ip domain-lookup  
SW1(config)# line vty 0 4  
SW1(config-line)# history size 15  
SW1(config-line)# exec-timeout 10 30  
SW1(config-line)# logging synchronous
```

### Saving configuration

```
SW1# copy running-config nutty  
! Destination filename [nutty]  
SW1# wr
```

### Description, speed and duplex

```
SW1(config)# interface fastEthernet 0/1  
SW1(config-if)# description LINK TO  
INTERNET ROUTER  
SW1(config-if)# speed 100 ! Options: 10, 100,  
auto  
! The range keyword used to set a group of  
interfaces at once.
```

### Description, speed and duplex (cont)

```
SW1(config)# interface range fastEthernet 0/5  
- 10
```

```
SW1(config-if-range)# duplex full (options: half,  
full, auto)
```

### Setting the default gateway

```
SW1(config)# ip default-gateway 172.16.1.1
```

### Securing console port

```
SW1(config)# line con 0  
SW1(config-line)# password cisco  
SW1(config-line)# login
```

### Aliases

! Used to create shortcuts for long commands.  
SW1(config)# alias exec c configure terminal

### Securing terminal lines

```
SW1(config)# line vty 0 4  
SW1(config-line)# password cisco  
SW1(config-line)# login
```

### Configuring banners

```
SW1(config)# banner motd $
```

### Giving the switch an IP address

```
SW1(config)# interface vlan 1  
SW1(config-if)# ip address 172.16.1.11  
255.255.255.0 ! or DHCP  
SW1(config-if)# no shutdown
```

### Configuring switch to use SSH

► **Configure DNS domain name :**

```
SW1(config)# ip domain-name example.com
```

► **Configure a username and password :**

```
SW1(config)# username admin password  
cisco
```

► **Generate encryption keys :**

! The size of the key modulus in the range of 360 to 2048

```
SW1(config)# crypto key generate rsa
```

How many bits in the modulus [512]: 1024

► **Define SSH version to use :**

```
SW1(config)# ip ssh version 2
```

► **Enable vty lines to use SSH :**

```
SW1(config)# line vty 0 4
```

```
SW1(config-line)# login local
```

! You can set vty lines to use only telnet or only ssh or both as in the example.

```
SW1(config-line)# transport input telnet ssh
```

### Verify Basic Configuration

► Shows information about the switch and its interfaces, RAM, NVRAM, flash, IOS, etc

```
SW1# show version
```

► Shows the current configuration file stored in DRAM.

```
SW1# show running-config
```

► Shows the configuration file stored in NVRAM which is used at first boot process.

```
SW1# show startup-config
```

► Lists the commands currently held in the history buffer.



### Verify Basic Configuration (cont)

#### SW1# **show history**

- ▶ Shows an overview of all interfaces, their physical status, protocol status and ip address if assigned.

#### SW1# **show ip interface brief**

- ▶ Shows detailed information about the specified interface, its status, protocol, duplex, speed, encapsulation, last 5 min traffic.

#### SW1# **show interface vlan 1**

- ▶ Shows the description of all interfaces

#### SW1# **show interfaces description**

- ▶ Shows the status of all interfaces like connected or not, speed, duplex, trunk or access vlan.

#### SW1# **show interfaces status**

- ▶ Shows the public encryption key used for SSH.

#### SW1# **show crypto key mypubkey rsa**

- ▶ Shows information about the leased IP address (when an interface is configured to get IP address via a dhcp server)

#### SW1# **show dhcp lease**



By [kanisthaw](#)

[cheatography.com/kanisthaw/](http://cheatography.com/kanisthaw/)

Published 7th June, 2016.

Last updated 7th June, 2016.

Page 2 of 2.

Sponsored by [CrosswordCheats.com](#)

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>